Sida 3: [1] Ändra	Unknown

Ändrad fältkod

Sida 3: [2] Ändra	Unknown

Ändrad fältkod

Sida 3: [3] Ändra	Unknown

Ändrad fältkod

Sida 3: [4] Ändra	Unknown

Ändrad fältkod

Sida 3: [5] Ändra	Unknown

Ändrad fältkod

Sida 3: [6] Ändra	Unknown

Ändrad fältkod

Sida 3: [7] Ändra	Unknown

Ändrad fältkod

Sida 3: [8] Ändra	Unknown

Ändrad fältkod

Sida 3: [9] Ändra	Unknown

Ändrad fältkod

Sida 3: [10] Ändra	Unknown

Ändrad fältkod

Sida 3: [11] Ändra	Unknown

Ändrad fältkod

Sida 3: [12] Ändra	Unknown

Ändrad fältkod

Sida 3: [13] Ändra	Unknown

Ändrad fältkod

Sida 3: [14] Ändra	Unknown

Ändrad fältkod

Sida 3: [15] Ändra	Unknown

Ändrad fältkod

Sida 3: [16] Ändra	Unknown

Ändrad fältkod

Sida 3: [17] Ändra	Unknown

Ändrad fältkod

Sida 3: [18] Ändra	Unknown

Ändrad fältkod

Sida 3: [19] Ändra	Unknown

Ändrad fältkod

Sida 3: [20] Ändra **Unknown**

Ändrad fältkod

Sida 3: [21] Ändra **Unknown**

Ändrad fältkod

Sida 3: [22] Ändra **Unknown**

Ändrad fältkod

Sida 3: [23] Ändra **Unknown**

Ändrad fältkod

Sida 3: [24] Ändra **Unknown**

Ändrad fältkod

Sida 3: [25] Ändra **Unknown**

Ändrad fältkod

Sida 3: [26] Ändra **Unknown**

Ändrad fältkod

Sida 3: [27] Ändra **Unknown**

Ändrad fältkod

Sida 3: [28] Borttagen **Författare** **29/09/15 13:11**

5.2 OBJECTIVE 12
5.3 INPUTS 12
5.4 OUTCOME(S) 12
5.5 ENVIRONMENTAL NEEDS 12
5.6 SPECIAL PROCEDURAL REQUIREMENTS 12
5.7 INTERCASE DEPENDENCIES 12
5.8 ORDERED DESCRIPTION OF STEPS TO BE TAKEN TO EXECUTE THE TEST CASE 12

Sida 3: [29] Ändra **Unknown**

Ändrad fältkod

Sida 3: [30] Ändra **Unknown**

Ändrad fältkod

Sida 3: [31] Borttagen **Författare** **29/09/15 13:11**

6.2 OBJECTIVE 13
6.3 INPUTS 13
6.4 OUTCOME(S) 13
6.5 ENVIRONMENTAL NEEDS 13
6.6 SPECIAL PROCEDURAL REQUIREMENTS 13
6.7 INTERCASE DEPENDENCIES 13
6.8 ORDERED DESCRIPTION OF STEPS TO BE TAKEN TO EXECUTE THE TEST CASE 13

Sida 3: [32] Ändra **Unknown**

Ändrad fältkod

Sida 3: [33] Ändra **Unknown**

Ändrad fältkod

Sida 3: [34] Borttagen **Författare** **29/09/15 13:11**

7.2 OBJECTIVE 14
7.3 INPUTS 14

7.4 OUTCOME(S) 14
7.5 ENVIRONMENTAL NEEDS 14
7.6 SPECIAL PROCEDURAL REQUIREMENTS 14
7.7 INTERCASE DEPENDENCIES 14
7.8 ORDERED DESCRIPTION OF STEPS TO BE TAKEN TO EXECUTE THE TEST CASE 14

Sida 9: [35] Formaterad **Författare** **29/09/15 13:11**

Numrerad lista + Nivå: 2 + Numreringsformat: a, b, c, ... + Starta vid: 1 + Justering: Vänster + Justerad vid: 1,9 cm + Indrag vid: 2,54 cm

Sida 9: [36] Formaterat **Författare** **29/09/15 13:11**

Typsnitt:Kursiv, Svenska

Sida 9: [37] Formaterat **Författare** **29/09/15 13:11**

Typsnitt:Kursiv, Svenska

Sida 9: [38] Formaterat **Författare** **29/09/15 13:11**

Svenska

Sida 9: [39] Formaterat **Författare** **29/09/15 13:11**

Svenska

Sida 9: [40] Borttagen **Författare** **29/09/15 13:11**

MUST be present in the response.
The key/value pairs MUST begin with the key, followed by a colon and the value. One on each line. Spacing is optional.

A legal disclaimer MUST be present somewhere

a.

Sida 9: [41] Formaterat **Författare** **29/09/15 13:11**

Svenska

Sida 9: [42] Formaterat **Författare** **29/09/15 13:11**

Svenska

Sida 9: [43] Formaterat **Författare** **29/09/15 13:11**

Svenska

Sida 9: [44] Borttagen **Författare** **29/09/15 13:11**

The values of EPP keywords MUST follow the requirements given in the Test Plan. The comparison should be case insensitive.

Sida 9: [45] Borttagen **Författare** **29/09/15 13:11**

Multiple queries will be performed over IPv4 TCP connections on port 43. The objective is to verify the format of the responses.

Inputs

The following information will be needed as input for this test case:

Id	Description	Type
TLD	The ASCII compatible name of the TLD	String
WhoisTestRegistrar	An existing registrar which has Whois data	String

Sida 9: [46] Borttagen **Författare** **29/09/15 13:11**

The format of the responses MUST follow a semi-free text format, as outlined in section 2.1.3.2 of the Whois Test Plan.

Environmental needs

Whois client software
IPv4 connectivity
<WhoisIPv4> from resolving <whois.nic.TLD> using the delegation data.

Special procedural requirements

Abort the test if any

Sida 9: [47] Formaterad	Författare	29/09/15 13:11

Liststycke,Punktlista + Nivå: 1 + Justerad vid: 0,63 cm + Indrag vid: 1,27 cm

Sida 9: [48] Flyttad till sidan 6 (Flytta #1)	Författare	29/09/15 13:11

Intercase dependencies

This test has no intercase dependencies.
Ordered description of steps

Sida 9: [49] Formaterat	Författare	29/09/15 13:11

Engelska (USA)

Sida 9: [50] Formaterat	Författare	29/09/15 13:11

Engelska (USA)

Sida 9: [51] Borttagen	Författare	29/09/15 13:11

Make a query from each test node using the client software.
whois -h **<WhoisIPv4>** "registrar **<WhoisTestRegistrar>**"
Do a check if the response matches the format given in Whois TP, section 2.1.3.3.
The queried registrar name MUST be present in the response.
The key/value pairs MUST begin with the key, followed by a colon and the value. One on each line. Spacing is optional.
A legal disclaimer MUST be present somewhere in the response. The disclaimer SHOULD be at the end of the response.
The values of EPP keywords MUST follow the requirements given in the Test Plan. The comparison should be case insensitive.

Sida 11: [52] Borttagen	Författare	29/09/15 13:11

. At least one of them MUST give response with Whois data.

Sida 11: [53] Formaterad	Författare	29/09/15 13:11

Formaterad

Sida 11: [54] Formaterat	Författare	29/09/15 13:11

Typsnitt:Kursiv, Svenska

Sida 11: [55] Formaterat	Författare	29/09/15 13:11

Typsnitt:Kursiv, Svenska

Sida 11: [56] Borttagen	Författare	29/09/15 13:11

The queried name server MUST be present in

a.

Sida 11: [57] Formaterat	Författare	29/09/15 13:11

Svenska

Sida 11: [58] Borttagen	Författare	29/09/15 13:11

.

The key/value pairs MUST begin with

b.

Sida 11: [59] Borttagen	Författare	29/09/15 13:11

key, followed by a colon and the value. One on each line. Spacing is optional.

c.

Sida 11: [60] Borttagen	Författare	29/09/15 13:11

A legal disclaimer MUST be present somewhere in the

i.

Sida 11: [61] Formaterat	Författare	29/09/15 13:11

Svenska

Sida 11: [62] Formaterad	Författare	29/09/15 13:11

Formaterad

Sida 11: [63] Borttagen	Författare	29/09/15 13:11

The values of EPP keywords MUST follow

ii.

Sida 11: [64] Formaterad	Författare	29/09/15 13:11

Punktlista + Nivå: 1 + Justerad vid: 0,63 cm + Indrag vid: 1,27 cm

Sida 12: [65] Borttagen	Författare	29/09/15 13:11

Objective

Multiple queries will be performed over IPv6 TCP connections on port 43. The objective is to verify the format of the responses.

Inputs

The following information will be needed as input for this test case:

Id	Description	Type
TLD	The ASCII compatible name of the TLD	String
WhoisTestDomain	An existing domain name which has Whois data	String

Outcome(s)

The format of the responses MUST follow a semi-free text format, as outlined in section 2.1.3.1 of the Whois Test Plan.

Environmental needs

Whois client software

Sida 12: [66] Borttagen	Författare	29/09/15 13:11

<WhoisIPv6> from resolving <whois.nic.TLD> using the delegation data.

Special procedural requirements

Abort the test if any Whois query takes longer than 10 seconds.

Intercase dependencies

This test has no intercase dependencies.

Ordered description of steps to be taken to execute the test case

Make a query from each test node using the client software.
whois -h **<WhoisIPv6> <WhoisTestDomain>**
Do a check if the responses match the format given in Whois TP, section 2.1.3.1.
The queried domain name MUST be present in the response.
The key/value pairs MUST begin with the key, followed by a colon and the value. One on each line. Spacing is optional.
A legal disclaimer MUST be present somewhere in the response. The disclaimer SHOULD be at the end of the response.
The values of EPP keywords MUST follow the requirements given in the Test Plan. The comparison should be case insensitive.

Sida 13: [67] Borttagen	Författare	29/09/15 13:11

Objective

Multiple queries will be performed over IPv6 TCP connections on port 43. The objective is to verify the format of the responses.

Sida 13: [68] Borttagen	Författare	29/09/15 13:11

Outcome(s)

The format of the responses MUST follow a semi-free text format, as outlined in section 2.1.3.2 of the Whois Test Plan.

Environmental needs

Whois client software
IPv6 connectivity
<WhoisIPv6> from resolving <whois.nic.TLD> using the delegation data.

Special procedural requirements

Abort the test if any Whois query takes longer than 10 seconds.

Intercase dependencies

This test has no intercase dependencies.

Ordered description of steps to be taken to execute the test case

Make a query from each test node using the client software.
whois -h **<WhoisIPv6>** "registrar **<WhoisTestRegistrar>**"
Do a check if the response matches the format given in Whois TP, section 2.1.3.2.
The queried registrar name MUST be present in the response.
The key/value pairs MUST begin with the key, followed by a colon and the value. One on each line. Spacing is optional.
A legal disclaimer MUST be present somewhere in the response. The disclaimer SHOULD be at the end of the response.
The values of EPP keywords MUST follow the requirements given in the Test Plan. The comparison should be case insensitive.

Sida 14: [69] Borttagen **Författare** **29/09/15 13:11**

Objective

Multiple queries will be performed over IPv6 TCP connections on port 43. The objective is to verify the format of the responses.

Inputs

The following information will be needed as input for this test case:

Id	Description	Type
TLD	The ASCII compatible name of the TLD	String
WhoisTestNameServerName	The domain name of an existing name server which has Whois data	String
WhoisTestNameServerIP	The IP address of an existing name server which has Whois data	String

Outcome(s)

The format of the responses MUST follow a semi-free text format, as outlined in section 2.1.3.3 of the Whois Test Plan.

Environmental needs

Whois client software

Sida 14: [70] Borttagen **Författare** **29/09/15 13:11**

<WhoisIPv6> from resolving <whois.nic.TLD> using the delegation data.

Special procedural requirements

Abort the test if any Whois query takes longer than 10 seconds.

Intercase dependencies

This test has no intercase dependencies.

Ordered description of steps to be taken to execute the test case

Make two queries from each test node using the client software. At least one of them MUST give a response with Whois data.
whois -h **<WhoisIPv6> <WhoisTestNameServerName>**
whois -h **<WhoisIPv6>** "nameserver **<WhoisTestNameServerIP>**"
For each positive response, do a check if the response matches the format given in Whois TP, section 2.1.3.3.

The queried name server MUST be present in the response.
The key/value pairs MUST begin with the key, followed by a colon and the value. One on each line. Spacing is optional.
A legal disclaimer MUST be present somewhere in the response. The disclaimer SHOULD be at the end of the response.

The values of EPP keywords MUST follow the requirements given in the Test Plan. The comparison should be case insensitive.